



KS-20



CNC Sliding Head Swiss Lathe with FANUC Oi-TD Controller

- ◆ Sliding head design
- ◆ Rotary guide bushing to increase stability when machining long work piece
- ◆ Main and sub-spindle feature C-axis functions
- ◆ Direct drive spindle
- ◆ 4 sets of tool slides
- ◆ 0.79" (20mm) maximum turning diameter
- ◆ 8.07" (205mm) maximum turning length

Starting at: \$130,000

KS-32



Sliding Head & Fixed Head Compound CNC Lathe

- ◆ Sliding head design
- ◆ Rotary guide bushing to increase stability when machining long work piece
- ◆ Main and sub-spindle feature C-axis functions
- ◆ Direct drive spindle
- ◆ 4 sets of tool slides
- ◆ 1.26" (32mm) maximum turning diameter
- ◆ 11.81" (300mm) maximum turning length

Starting at: \$165,000

TM-764



Vertical Machining Center w/ FANUC Oi-MD Controller

- ◆ 30" x 16" x 22" travel
- ◆ 32" x 16" table size
- ◆ CAT-40 spindle taper
- ◆ Direct drive spindle
- ◆ Precision linear guides and ball screws
- ◆ 12,000 rpm spindle speed
- ◆ 1890 ipm raid traverse
- ◆ Rigid tapping
- ◆ 20-tool arm type ATC
- ◆ 10 HP spindle motor

Starting at: \$72,000

T-8



CNC Hybrid Turret Lathe w/ Mitsubishi M700 Controller

- ◆ Duo system with power turret and gantry tools system
- ◆ Run 2 programs simultaneously to save cycle time
- ◆ Synchronous spindles
- ◆ Flexible gang tooling system with rotary tables class-B-axis for machining on sub-spindle
- ◆ Free angle B-axis 360° for all angular drilling and tapping
- ◆ 12-station power turret
- ◆ Up to 24 live tools

Starting at: \$230,000





LM-6



CNC Slant Bed Lathe w/ FANUC Oi-TD Controller

- ◆ A2-6 spindle nose
- ◆ 15" (380 mm) maximum turning diameter
- ◆ 16.1" (409 mm) maximum turning length
- ◆ Programmable hydraulic tailstock
- ◆ High precision ball screw & linear guide
- ◆ Dynamic graphic display
- ◆ High speed 12-station servo turret
- ◆ 1,181 ipm rapid traverse
- ◆ 6,000 rpm spindle speed

Starting at: \$69,800

LM-8A



CNC Slant Bed Lathe w/ FANUC Oi-TD Controller

- ◆ A2-6 spindle nose
- ◆ 15" (380 mm) maximum turning diameter
- ◆ 15.4" (390 mm) maximum turning length
- ◆ Programmable hydraulic tailstock
- ◆ High precision ball screw & linear guide
- ◆ Dynamic graphic display
- ◆ High speed 12-station servo turret
- ◆ 1,181 ipm rapid traverse
- ◆ 4,500 rpm spindle speed

Starting at: \$75,000

LM-8B/10A



CNC Slant Bed Lathe w/FANUC Oi-TD Controller

- ◆ FANUC Oi-TD controller
- ◆ 3-jaw hydraulic chuck (soft & hard jaw-1 set each)
- ◆ Servo turret (cap. 12T)
- ◆ Fully enclosed splash guard
- ◆ Working light
- ◆ Warning light
- ◆ Hydraulic system
- ◆ Coolant system
- ◆ Auto lubrication system
- ◆ Tool kit

Starting at: \$72,000

XT-326L



S2 Hydrodynamic Automatic Bar Feeder

- ◆ Unique appearance with multi-bending exterior cover
- ◆ PU guiding elements minimize vibration noise and are easily replaced
- ◆ Powerful clamping capacity for bar insertion and extraction
- ◆ Loading mechanism changeover simplicity
- ◆ PLC controlled operation
- ◆ I/O interfacing with any NC or CNC type lathe

Starting at: \$16,000

