



## XT-326L S2 Hydrodynamic Automatic Barfeeder



### Standard Features:

- ◆ Unique appearance with multi-bending exterior cover
- ◆ PU guiding elements minimize vibration noise and are easily replaced
- ◆ Powerful clamping capacity for bar insertion and extraction
- ◆ Loading mechanism changeover simplicity
- ◆ PLC controlled operation. Parameter setting ensure optimal function for every application. Alarm messages allow convenient trouble shooting
- ◆ I/O interfacing with any NC or CNC type lathe
- ◆ Hand hold remote control combined with HMI provides maximum operation convenience (optional)

**Starting at: \$16,000**



# Technical Data

Specifications	◆ Diameter		◆ 3-26 mm
	◆ Bar Length	8.2'/10.50'/12.14'/13.12'	◆ 2600mm/3230mm/3790mm/4230mm
	◆ Loading system	Side load rack	
	◆ Loading capacity	.10.63"	
	◆ Loading and feeding side	LtoRF/RtoLF	
	◆ Headstock type	Fixed/sliding	
	◆ Synchronisation (optional)	Electronic Synchronization	
	◆ Front rest	Manual	
	◆ Drive	Servo motor	
	◆ Guiding	Hydrodynamic U-Channel	
	◆ Weight	776lb/815.7lb/850.9lb/884lb	352kg/370kg/386kg/401kg

**Design and specifications are subject to change without notice**

Channel Size	Pusher Size	Bar Size	Spindle Size
8	7	(3)~8	8
11	10	(3)~10	11
14	13	(4)~13	14
16	15	(4)~15	16
17	16	(4)~16	17
19	18	(4)~18	19
21	20	(5)~20	21
23	22	(5)~22	23
25	24	(5)~24	25
27	26	(5)~26	27